H2FUTURE – Hydrogen Electrolysis

HYDROGEN MEETING FUTURE NEEDS OF LOW CARBON MANUFACTURING VALUE CHAINS

08.10. 2019 Hermann Wolfmeir



This project has received funding from the Fuel Cells and Hydrogen 2 Joint Undertaking under grant agreement No 735503. This Joint Undertaking receives support from the European Union's Horizon 2020 research and innovation programme and Hydrogen Europe and N.ERGHY




voestalpine Stahl GmbH www.voestalpine.com/stahl



H2FUTURE PROJECT IDFA

» TODAY: Hydrogen is produced via steam reformation from fossil fuels, mostly from natural gas. This leads to substantial CO₂ emissions.



» IN THE FUTURE: Water electrolysis via electricity from renewable energy sources will be the main source of green hydrogen with a minimal CO₂ footprint.



voestalpine
ONE STEP AHEAD.


TECHNOLOGIES READY TO THE MARKET

Alkaline Electrolysis


 $2OH^- \rightleftharpoons \frac{1}{2}O_2 + H_2O + 2e^-$ Anode:

Cathode: $2H_2O + 2e^- \rightleftharpoons H_2 + 2OH^-$

 $H_2O \rightleftharpoons H_2 + \frac{1}{2}O_2$ Total:



PEM – Electrolysis (proton exchange membrane)



 $H_2O \rightleftharpoons 2H^+ + \frac{1}{2}O_2 + 2e^-$ Anode:

Cathode: $2H^+ + 2e^- \rightleftharpoons H_2$

Solid electrolyte: perflourosulfonated polymer

 $H_2O \rightleftharpoons H_2 + \frac{1}{2}O_2$ Total:

- More than 100 years of development history
- Life time up to 40 years at stable operation
- Up to 5 MW, high efficiency
- Liquid electrolyte 20-25% KOH
- Low dynamics
- No partial load<30%
- Current densities 0,25 A/cm²





- membrane (e.g. Nafion ®) High current densities up 2 A/cm²
- High dynamics, load range 10 to 100%
- Number of suppliers for plants > 1MW modest
 - Life time?

voestalpine Stahl GmbH

10/08/2019

H2FUTURE Carmo et al.: A comprehensive review on PEM water electrolysis, Int. J. Hydrogen Energy, 38 (2013) Friedrich; Zukunftspotenziale der Elektrolyse; Univ. Stuttgart




EU HORIZON 2020 CALL FOR TENDER: CALL FCH-02-7-2016

SCOPE AND OBJECTIVES (1)



- » Design and installation of a 6 MW PEM (1200m³_n/h) electrolyser system
 - » The hydrogen purity should meet the application requirements...
 - » Storage and compression are not in the scope of this topic



- To demonstrate an energy consumption of 48 kWh/kg H₂ for PEM technology at nominal power
- » Ambitious efficiency target
- » $\eta_{\text{System}} = 82\%$

Source: Development of Water Electrolysis in the European Union FCH JU (2014)

voestalpine Stahl GmbH

4 | 10/08/2019




EU HORIZON 2020 CALL FOR TENDER: CALL FCH-02-7-2016

SCOPE AND OBJECTIVES (2)

- » Two year demonstration
- » To demonstrate a CAPEX for the of <1000 €/kW for PEM technology</p>
- » To develop a large scale electrolyser of sufficiently rapid response time (of the order of a few seconds), to participate in the existing primary and secondary grid balancing markets

Volatile generation and volatile demand



FUEL CELLS AND HYDROGEN

ONE STEP AHEAD.



10/08/2019

PROJECT OVERVIEW H2FUTURE





One of the biggest forthcoming PEM electrolyser units in the world with 6 MW power and 1200 m 3 /h H $_2$ production at voestalpine Linz for full scale demonstration of H $_2$ production and grid balancing





Project Budget: 17,8 M€

Total EU Funding: 12,0 M€ (70% funding)

Project Duration: 4,5 years (2017-2021)











© Siemens AG

voestalpine Stahl GmbH 6 | 10/08/2019 |

LOCATION SELECTION "BG 89 WASSERSTOFFANLAGE NORD"




- » voestalpine is in charge of providing the infrastructure
- » Location next to power station ensures availability of
 - » Electricity
 - » Cooling water
 - » Deionized water
 - » Nitrogen
 - » Pressurized air
 - » Connection to COG-network

voestalpine Stahl GmbH



BASIC & DETAIL ENGINEERING

» Principal layout of PEM-electrolyser system




Flow Chart: Smolink, PEM Water Electrolysis, Present Status of R&D, 18th world Hydrogen Conference, Essen, 18.05.2010



8 | 10/08/2019



LAYOUT OF PEM ELECTROLYSER SYSTEM TECHNICAL CHARACTERISTICS



At least 170 comparable units for supplying a DR-plant like Texas necessary

voestalpine Stahl GmbH

10/08/2019 **H2FUTURE** Rated power 6 MW

Hydrogen $1200 \, \text{m}^3_{(STP)}/\text{h}$

Oxygen $600 \, \text{m}^3_{(STP)}/\text{h}$

Cells 600 (12 x 50)

Membrane 0,5 m²/cell

Current density

Current

Voltage up to

Cooling Water

Pressure

Purity

Dew point

1 A/cm²

5000 A

2 V/cell $350 \, \text{m}^3/\text{h}$


max. 150 mbar

 $> 98 \% H_2$

< 10 °C







HYDROGEN STEELMAKING PROJECT STATUS H2FUTURE (2017-2021)







15.03.2018

02.07.2018

07.08.2018

» August 2018: Finalization electrolyzer building, delivery of transformer







H2FUTURE PROJECT STATUS H2FUTURE



October 2018:

assembly works transformer and rectifier

29.10.2018



September 2018:

installation of ventilation and cooling system



voestalpine

ONE STEP AHEAD.

voestalpine Stahl GmbH 12 | 10/08/2019 |

H2FUTURE PROJECT STATUS H2FUTURE



30.01.2019

November 2018 –

February 2019

Installation of heat exchangers assembly works, final piping works completion of infrastructure





13 10/08/2019



H2FUTURE



March / April 2019

Delivery of first 3 modules

voestalpine Stahl GmbH 10/08/2019

H2FUTURE





September 2019

Completion of first row



R&D OBJECTIVES OF VOESTALPINE IS PEM ELECTROLYSIS A RELIABLE TECHNOLOGY?



- » Systematic upscaling requires answers of following questions /topics
- » Operation of PEM electrolyser
 - a. operating range
 - b. Efficiency: Influence of dynamic operation, continuous and overload operation
 - c. Degradation of PEM due to ageing and poisoning
- » Durability considering the mode of operation
 - a. Maintenance intensity
 - b. Tightness
 - c. Corrosion
- » Quality of product and input reactant streams
 - a. Requirements deionized water
 - b. Quality of H₂ and O₂ dependent on operation mode
- Influence of operation time





Thank you! Questions?

Hermann Wolfmeir T. +43/50304/15-4310 hermann. wolfmeir@voestalpine.com

voestalpine Stahl GmbH www.voestalpine.com/stahl

